

<b>PRODUCT NAME</b>	<b>VİZYON APRICOT PASTRY FILLING</b>	
<b>PRODUCT DEFINITION</b>	Vizyon Pastry Fillings are prepared with fruit pieces and have a natural and delicious taste.	
<b>INGREDIENTS</b>	Apricot (30 %), Water, Sugar, Glucose Syrup, Thickener (Modified Corn Starch E1442, Pectin E440), Acidity Regulator (Citric Acid E330), Nature-Identical Apricot Flavor, Preservative (Potassium Sorbate E202), Colourant (Sunset Yellow E110).	
<b>DIRECTIONS FOR USE</b>	Vizyon Apricot Pastry Filling is suggested to be applied directly on cakes, cookies, pies and muffins to give them delicious taste and flavour.	
<b>PHYSICAL and CHEMICAL ANALYSIS</b>	<b>Colour</b>	Apricot Colour
	<b>Appearance</b>	Consistent Jelly With Fruit Pieces
	<b>Taste</b>	Characteristic Taste
	<b>Odour</b>	Characteristic Odour
	<b>Brix</b>	60 – 65 %
	<b>pH</b>	3,6 – 4,1
	<b>Water Activity (aw)</b>	Max. 0,90
<b>HEAVY METALS</b>	<b>Arsenic</b>	< 3 ppm
	<b>Mercury</b>	< 1 ppm
	<b>Lead</b>	< 10 ppm
	<b>Cadmium</b>	< 1 ppm
<b>MICROBIOLOGICAL ANALYSIS</b>	<b>Salmonella</b>	Absent in 25 g
	<b>L. monocytogenes</b>	Absent in 25 g
	<b>Termotolerant Campylobacter spp</b>	Absent in 25 g
	<b>E.coli</b>	Absent in 25 g
	<b>Coagulase positive staphylococci</b>	< 1 x 10 <sup>2</sup> cfu/g
	<b>B.cereus</b>	< 1 x 10 <sup>2</sup> cfu/g
	<b>Sulfite-reducing anaerob</b>	< 1 x 10 <sup>2</sup> cfu/g
<b>Yeast and Mold</b>	< 1 x 10 <sup>4</sup> cfu/g	
<b>ALLERGEN</b>	Does not contain.	
<b>REGULATIONS</b>	Turkish Food Codex	
	Joint Expert Committee for Food Additives (JECFA) and Food Chemicals Codex (FCC).	
<b>STORAGE</b>	Keep closed in a cool (25°C) and dry place.	
<b>SHELF LIFE</b>	12 months from production date.	



## PRODUCT DATA SHEET

Document Code	KY-US-214
Publication Date	04.02.2010
Revision Date	24.07.2013
Revision Number	05
Page Number	2 / 2

<b>PACKAGING</b>	The product is packaged according to Turkish Food Codex Packaging Regulations in 3 kg pails
<b>SHIPMENT</b>	Products should be shipped without any pest, pest residue, glass, wood, metal and foreign material. Upper side of the vehicle should be closed with clean calash during transport.
<b>COMPANY REGISTRATION</b>	TR-34-K-002719
<b>QUALITY SYSTEM</b>	<b>ISO 22000</b>  